

## 50-54 MHz

Please note that this bandplan is a general recommendation. Spectrum usage can be different depending on location and regional coordination differences. Please check with your Frequency Coordinator for information.

|               |  |
|---------------|--|
| 50.0-50.1     | CW, beacons                            |
| 50.060-50.080 | beacon subband                         |
| 50.1-50.3     | SSB,CW                                 |
| 50.10-50.125  | DX window                              |
| 50.125        | SSB calling                            |
| 50.3-50.6     | all modes                              |
| 50.4          | AM calling frequency                   |
| 50.6-50.8     | nonvoice communications                |
| 50.62         | digital (packet) calling               |
| 50.8-51.0     | radio remote control (20-kHz channels) |

NOTE: Activities above 51.10 MHz are set on 20-kHz-spaced "even channels"

|              |  |
|--------------|--|
| 51.0-51.1    | Pacific DX window                              |
| 51.5-51.6    | simplex (6 channels)                           |
| 51.12-51.48  | repeater inputs (19 channels)                  |
| 51.12-51.18  | digital repeater inputs                        |
| 51.62-51.98  | repeater outputs (19 channels)                 |
| 51.62-51.68  | digital repeater outputs                       |
| 52.0-52.48   | repeater inputs (except as noted; 23 channels) |
| 52.02, 52.04 | FM simplex                                     |
| 52.2         | TEST PAIR (input)                              |